



- GENERAL NOTES FLOOR PLAN**
- DO NOT SCALE DRAWINGS
 - DIMENSIONS ON WALLS ARE GIVEN TO THE OUTSIDE FACE OF THE WALL FINISH UNLESS OTHERWISE NOTED.
 - PLEASE SEE SHEET A8.1 FOR DOOR INFORMATION.
 - PLEASE SEE SHEET A8.2 AND A.8.3 FOR WINDOW INFORMATION
 - PLEASE SEE SHEET A0.2 FOR PARTITION TYPES.
 - PARTITIONS ARE TO BE TYPE A3 UNLESS OTHERWISE NOTED.
 - REGULG SEALANT JOINTS BETWEEN EXISTING EXTERIOR MASONRY WALLS AND EXISTING STOREFRONT SYSTEM, EXISTING WALLS AND EXISTING EXTERIOR SOFFIT, AND ALL MISCELLANEOUS UTILITY PENETRATIONS.
 - JAMBS FOR DOORS LOCATED ADJACENT TO A PERPENDICULAR WALL ARE 4" FROM THE FACE PERPENDICULAR WALL FACE UNLESS SPECIFICALLY NOTED OTHERWISE.
 - PROVIDE CRICKETS AS REQUIRED FOR PROPER DRAINAGE AT ALL ROOF CURB LOCATIONS.
 - ARROWS ON ROOF SURFACES INDICATE DOWNWARD SLOPE OF ROOF.

- KEY NOTES**
- MILLWORK- SEE MILLWORK DRAWINGS
 - PROVIDE FRONT OPENING, LOCKING, ALUMINUM AND GLASS DISPLAY CASE DOOR IN WALL. SIZE IS 3' WIDE AND 5' TALL. MOUNT 2' A.F.F.
 - 20" L.O.D DISPLAY SCREEN MOUNTED IN WALL FACE WITH PROTECTIVE GLASS COVER. PROVIDE ACTIVATION SWITCH IN STAINLESS STEEL COVER PLATE ADJACENT TO SCREEN.
 - PREFABRICATED ALUMINUM DIRECTORY WITH 4 COLOR SILKSCREENED GRAPHICS. DIRECTORY SIZE TO BE 18" WIDE AND 30" TALL.
 - PREFINISHED PREFABRICATED ALUMINUM COLUMN COVER.
 - PROVIDE GWB TRIMMED OPENINGS FOR ACCESS TO RECYCLED MATERIAL BINS.
 - PROVIDE BUILT IN RECEPTION DESK. WOOD VENEER FINISH. WORKING SURFACE TO BE PLASTIC LAMINATE. TRANSACTION COUNTER TO BE PLASTIC LAMINATE.
 - PAINTED STEEL GUARDRAIL WITH PAINTED STEEL MESH INFILL AND PAINTED STEEL TOP RAIL. MESH TO BE 202 X 104" AS MANUFACTURED BY AMETCO
 - PAINTED STEEL STAIRS WITH WOOD TREADS
 - EXISTING GWB COLUMN SURROUND TO REMAIN. INSTALL FURRED WALL PARTITION SHOWN OVER EXISTING SURROUND.
 - NEW HYDRAULIC TWO STOP ELEVATOR, CAB, AND SHAFT. CAB FINISHES TO BE MANUFACTURER STANDARD
 - ACOUSTICAL FOLDING PARTITION WITH FABRIC FACES.
 - SLIDING TRANSACTION WINDOW.
 - PAINTED STEEL STAIRS WITH RUBBER TREADS
 - NOT USED
 - PAINTED STEEL ROOF ACCESS LADDER
 - PAINTED STEEL ELEVATOR PIT ACCESS LADDER
 - INTERIOR STOREFRONT GLAZING SYSTEM WITH DECORATIVE GLASS.
 - ENERGY SYSTEM MANAGEMENT FLAT PANEL DISPLAY MONITORS.
 - NEW ROOF HATCH
 - EXISTING ROOF HATCH. CLEAN, REPLACE SEALS, AND REPAINT.
 - PROVIDE 2" RIGID INSULATION OVER ENTIRE DECK.
 - PROVIDE HIGH EMISSIVITY TPO MECHANICALLY ATTACHED ROOF MEMBRANE OVER ENTIRE DECK. 60 MIL THICKNESS MINIMUM.
 - PROVIDE PREFORMED ALUMINUM ROOF COPING
 - ROOFTOP MECHANICAL UNIT. SEE MECHANICAL DOCUMENTS FOR ADDITIONAL INFORMATION.
 - LOCATION OF ROOFTOP PV SYSTEM- OWNER PROVIDED ITEM
 - ROOF SCUPPER.
 - RECESSED LOCKABLE ACCESS PANEL IN WALL FOR FIRE PROTECTION PIPING.
 - LINE ABOVE
 - 9" TALL WOOD VENEER FOLDING DOOR SYSTEM WITH CONTINUOUS HINGES.
 - FLOOR TO CEILING ALUMINUM STOREFRONT SYSTEM. SEE INTERIOR WINDOW ELEVATIONS.
 - DOOR ACCESS CARD READER PEDESTAL LOCATION.
 - LINE BELOW
 - PLASTIC LAMINATE BREAK COUNTER. MOUNT TO KNEE WALL AT 34" A.F.F.
 - ALUMINUM AND GLASS GUARDRAIL SYSTEM.
 - ROOF MEMBRANE WALKWAY MEMBRANE.

ASHRAE HEADQUARTERS
ADDITION AND RENOVATION

© COPYRIGHT
RICHARD WITTSCHIE ARCHITECTS, INC. AND IS NOT TO
BE REPRODUCED OR TRANSMITTED IN ANY
FORM OR BY ANY MEANS, ELECTRONIC OR
MECHANICAL, INCLUDING PHOTOCOPYING,
RECORDING, OR BY ANY INFORMATION
SYSTEM. NOT VALID UNLESS SIGNED AND SEALED.

LEVEL 2 FLOOR PLAN

200614

05/25/07

.A2.2

LEVEL 2 FLOOR PLAN

1/8" = 1'-0"

